

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.


Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	2 AWG
Wire Type	Stranded Copper; Class B; Compact, Compressed or Concentric, Class C; Concentric
Wire Strip Length	1-1/4 in.
Stud Size	1/2 in.
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90 ° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	BROWN
Panduit Die Index No. on Barrel	P33
Alternate Industry Die Index No. () on Barrel	(10)



CERTIFIED



LISTED Wire Connector



PANDUIT		CORP. TINLEY PARK, ILLINOIS	
		LCB2-12-Q	
		Copper Lug - One-Hole, Long Barrel	
REV	DATE	BY	CHK
00	12/08	JHNU	JHNU
		RELEASED	
		DESCRIPTION	
		ECN	SCALE
		N/A	N/A
		DRAWING NO / CAD FILE	LCB2-12-CUST